



## 3200 Series - Aluminum Impact Resistant Casement Window

- Heavy-duty all aluminum construction.
- Drip Cap built into header to prevent water intrusion.
- Extruded aluminum glazing bead.
- Multi-point full perimeter vent weatherstripping for energy efficiency - Meets FBC's 2014 Energy Code.
- Comes with full screen with Extended Aluminum Frame for maximum fresh air ventilation.
- Standard stainless steel components, fold-away roto handle and multi-point locking system for ultimate security.
- Profile extruded aluminum muntins. Optional stainless steel package available.
- Flange type frame for masonry construction.
- Available in X and XX configurations.
- Available in clear glass standard, High Performance IG LoE 366 & monolithic LoE 62/27, and tinted interlayer colors of gray, bronze, green, white or blue. Custom glass types, double or triple interlayer tints are available as a special order. Available in energy-efficient insulated laminated glass.
- Available in 1/1, 2/2, Brittany, Colonial and Custom Lite styles.
- Available in White or Bronze powder coat painted finishes.
- Available in standard and special window sizes.
- Passes tough South Florida Missile Impact Code.
- Meets HVHZ standards. Meets or exceeds FL#27559-1 Miami-Dade County NOA and FBC Building Codes.
- Meets AAMA 1302.5-1976 Code for Forced Entry Resistance.

# 3200 Series - Aluminum Impact Resistant Casement Window

CW-12	19-1/8" x 26"	X
CW-13	19-1/8" x 38-3/8"	X
CW-14	19-1/8" x 50-5/8"	X
CW-15	19-1/8" x 63"	X
CW-16	19-1/8" x 74-1/4"	X

CW-H32	26-1/2" x 26"	X
CW-H33	26-1/2" x 38-3/8"	X
CW-H34	26-1/2" x 50-5/8"	X
CW-H35	26-1/2" x 63"	X
CW-H36	26-1/2" x 74-1/4"	X

CW-22	37" x 26"	X
CW-23	37" x 38-3/8"	X
CW-24	37" x 50-5/8"	X
CW-25	37" x 63"	X
CW-26	37" x 74-1/4"	X

CW-32	53-1/8" x 26"	XX
CW-33	53-1/8" x 38-3/8"	XX
CW-34	53-1/8" x 50-5/8"	XX
CW-35	53-1/8" x 63"	XX
CW-36	53-1/8" x 74-1/4"	XX


CW-D22	74" x 26"	XX
CW-D23	74" x 38-3/8"	XX
CW-D24	74" x 50-5/8"	XX
CW-D25	74" x 63"	XX

\* X Units available is Hinge Left or Hinge Right  
 Note: Exterior View (reference point)  
 Also available in standard modular sizes


## SPECIFICATIONS

Maximum Size	37" x 74-1/4" X, 74" x 63" XX
Maximum Design Pressure	+70 / -82 PSF
Glass Thickness	5/16", 7/16" or 11/16" IG
Muntin	Profile Exterior/Flat Interior
Frame Color	White, Bronze
Frame Depth	2-1/4"
Miami-Dade County NOA	Refer to lawsonwindows.com


## Glazing Styles



FULL VIEW




COLONIAL




BRITTANY

## Lite Styles



IG GBG




RAISED PYRAMID/  
FLAT GRID

## Glazing Colors (OTHER COLORS, TEXTURES & GLASS TYPES AVAILABLE AS CUSTOM ORDER)



CLEAR



GREY  
INTERLAYER



BRONZE  
INTERLAYER



GREEN  
INTERLAYER



BLUE  
INTERLAYER



WHITE  
INTERLAYER




GRAY/WHITE  
INTERLAYER




LoE366



LoE6727



LoE6727 +  
GREY INTERLAYER



LoE6727 +  
WHITE/GREY INTERLAYER

